



AXTXM

Mini RF Camera Transmitter

RF Frequency Bands	2GHz to 7.1GHz
Camera RF Output	Selectable to 10, 50, 100mW
DVB-T Bandwidth	6,7,8MHz
DVB-T Guard	1/32, 1/16, 1/8, 1/4
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T Constellations	QPSK, 16QAM, 64QAM
Video Input	Composite, SD/HD-SDI, HDMI (Type A)
Compression Type	AVC/H.264/MEPG-4 Part 10
Encoder Latency	20mS In Ultra Low Delay
Encoder Bitrates	0.25 to 31Mb/s COFDM
Audio Inputs	SD/HD-SDI Embedded, HDMI 2 Digital Stereo Pairs 1x Analog Stereo Pair, 2 Channels Stereo or Mono
Power – DC Input	6 to 17VDC
Power Consumption	10W
Battery Plate	Canon BP-900 Series Battery Plate
Dimensions	L:4.76in / W:2.36in / H:3.61in



HD Resolutions

1920x1080i 60/59.94/50Hz
 1920x1080p 30/29.97/25/24/23.97Hz
 1920x1080psf 30/29.97/25/24/23.97Hz
 1280x720p 60/59.94/50Hz

SD Resolutions

720x480i 59.94Hz, 720x576i 50Hz

99 Garden Parkway Suite C, Carlisle, PA 17013
 PH: 1.888.736.9283

www.wavecentralrf.com

111016-A

Specifications subject to
 Change without prior notice.